

PLANOCOLOR VENETICO

DECLARATION OF PERFORMANCE

No. **C06239-CPR-2170032**

1. Unique identification code of the product type: **PLANOCOLOR VENETICO**

2. Intended use/s: **General purpose rendering mortar (GP) for internal and external use**

3. Manufacturer: **DOMOCHEMICAL S.A.
Papanikoli 40
15232 Chalandri, Athens
+30 210 6893954
novamix@novamix.gr
www.novamix.gr**

4. Authorised representative:

5. System/s of AVCP: **System 4**

- 6a. Harmonised standard: **EN 998-1:2016**

- Notified body/ies: **-**

PLANOCOLOR VENETICO


7. Declared performance/s:

Essential characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Class F	
Compressive strength	CS IV	
Adhesion	≥ 1,0 N/mm ² , FP: B	
Capillary water absorption	W _{c1}	EN 998-1:2016
Water vapour permeability coefficient (μ)	≤ 20	
Thermal conductivity mean λ _{10,dry,mat} values	0,33 W/mK	
Durability	Comply with 5.3.2	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Thiva, 15/12/2021



Dr. Plumis Papayassiliou
R&D/QC Manager

End of information as required by Regulation (EU) No 305/2011 & 574/2014

PLANOCOLOR VENETICO



15

ΔΟΜΟΧΗΜΙΚΗ Α.Β.Ε.Ε.
ΠΑΠΑΝΙΚΟΛΗ 40, 15232 ΧΑΛΑΝΔΡΙ, ΑΘΗΝΑ
DOMOCHEMICAL S.A.
ΡΑΠΑΝΙΚΟΛΙ 40, 15232 CHALANDRI, ATHENS

EN 998-1:2016
PLANOCOLOR VENETICO
DoP No.: C06239-CPR-2170032

Επίχρισμα γενικής χρήσης (GP) για εσωτερική και εξωτερική εφαρμογή
General purpose rendering mortar (GP) for internal and external use

Αντίδραση στη φωτιά	Reaction to fire	F
Θλιπτική αντοχή	Compressive strength	CS IV
Πρόσφυση	Adhesion	≥ 1,0 N/mm ² , FP: B
Τριχοειδής απορρόφηση νερού	Capillary water absorption	W _{c1}
Συντελεστής διάχυσης υδρατμών (μ)	Water vapour permeability coefficient (μ)	≤ 20
Συντελεστής θερμικής αγωγιμότητας λ _{10,ξηρό}	Thermal conductivity mean λ _{10,dry,mat} values	0,33 W/mK
Ανθεκτικότητα	Durability	Σύμφωνα με 5.3.2 Comply with 5.3.2